

CFD Analysis of a Gasoline Engine Exhaust Pipe

Pengyun Xu*, Haiyong Jiang and Xiaoshun Zhao

Mechanical and Electronical Engineering College, Agriculture University of Hebei, Baoding 071001, P.R. China

Abstract

The exhaust pipe is an important part of gasoline engine. Its structure and performance have a direct impact on the engine power, economy and emissions, and it is one of the key technologies of multi valve engine development. In order to test the theoretical design of a 1.5 L gasoline engine exhaust pipe, Solidworks Flow simulation was used to analyze the exhaust pipe. Pressure and velocity of the position near the three-way catalytic converter and the oxygen sensor were selective analyzed. CFD Simulation results show that the internal flow is laminar flow state, and the sensor position is reasonable. The design is reasonable, and can achieve the design goal.

Keywords: Exhaust pipe; Catalytic converter; Carrier component; Fluid uniformity; CFD analysis

Introduction

The exhaust pipe is an important part of gasoline engine. It connects all parts of the automobile exhaust system, and prevent the leakage of waste gas. Its structure and performance have a direct impact on the engine power, economy and emissions, and it is one of the key technologies of multi valve engine development.

Automobile exhaust pipe is a space curved surface geometry, it has a certain difficult to manufacture, and the exhaust pipe is worked in a bad condition, and some problems will occur in the process of production and use. The traditional design method of the exhaust pipe is in steady flow test stand experiments, to obtain or test shape parameter, this method takes long time and cost. However, using computer fluid analysis technology (CFD), it is convenient and intuitive to analyze the three-dimensional model of the exhaust pipe, the analysis process is visual, and easy to adjust the parameters, the analysis results are intuitive, determine whether the structure meets the design requirements quickly. In this paper, SolidWorks Flow Simulation is used to simulate the structure of a certain type of engine. Pressure and velocity of the position near the three way catalytic converter and the oxygen sensor were selective analyzed. The design goals are verified by simulation analysis (CFD) results.

In order to reduce the concentration of CO, NO_x and C_xH_y in the exhaust gas, there are (mostly) two catalytic converters installed in the exhaust pipe system. The crucial quantity to control the efficiency of a catalytic converter is the temperature in the catalytic converter. Due to this reason, one is interested in how to ensure a sufficient high temperature in the catalytic converters in a short time after the engine start. A special method of heating after the engine start is the combustion of unburnt gas in the catalytic converters. Modern cars can control the ratio of oxygen and fuel in the combustion chamber of the engine. By choosing a ratio with more fuel and less oxygen some unburnt fuel gets to the catalytic converters and can be used there for an exothermic reaction.

In order to test the theoretical design of a 1.5 L gasoline engine exhaust pipe, carrying out a natural experiment in respect gas flow hydrodynamics. To estimate the spectrum of possible technological innovations in the existing structure expedient, first carry out numerical simulations using fluid dynamics software packages solidworks flow simulation. This paper presents the numerical simulation of classical structure of exhaust pipe; the results are compared with the calculation for the case of a conical nozzle on the exhaust pipe [1-5].

Material and Methods

The calculation was carried out in gas dynamics software package Solidworks Cosmos FloWorks, which uses a finite volume method, the movement of the fluid is modeled by the Navier Stokes equations, the Reynolds averaged. Their closures are used for the transport equation and its kinetic energy dissipation within the k-ε turbulence model.

During the calculation was the condition of the grid and the iterative convergence, which were determined by the self-similarity of the final result of the number of cells and iterations.

Calculation of the motion of particles in the flow was conducted under the following assumptions:

- Uniform air and standard atmospheric pressure;
- The particles have a spherical shape;
- The drag coefficient of the particle is calculated by Henderson's equation;

A series of pertinent indoor and outdoor experiments are carried out to know the engineering properties of exhaust pipe, and provide theoretical references for engineering quality evaluation and improvement scheme selection.

3-D model analysis of exhaust pipe

Using SolidWorks software to establish the 3D model of the exhaust pipe, as shown in Figure 1. The model parameters are shown in Table 1.

In order to control the automobile harmful gases such as NO_x, HC and CO, the three-way catalytic converter must be installed in the exhaust pipe. The harmful gases can be converted into harmless carbon dioxide, water and nitrogen by oxidizing and reducing gases. The carrier component of the three-way catalytic converter is a porous ceramic material, which is installed in the specific position of the

*Corresponding author: Pengyun Xu, Mechanical and Electronical Engineering College, Agriculture University of Hebei, Baoding 071001, PR China, Tel: +86-0312-7526455; E-mail: pengyun99@qq.com

Received January 07, 2016; Accepted February 16, 2016; Published February 19, 2016

Citation: Xu P, Jiang H, Zhao X (2016) CFD Analysis of a Gasoline Engine Exhaust Pipe. J Appl Mech Eng 5:198. doi:10.4172/2168-9873.1000198

Copyright: © 2016 Xu P, et al. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

exhaust pipe, and is the most important equipment in the automobile ex-haust system. The three-way catalytic converter and oxygen sensor are generally installed in the exhaust manifold (natural gas engine) or after the turbocharger (turbocharged gasoline engine). The vector parameters and grid partition are shown in Tables 2 and 3. Grid partitioning result is shown in Figure 2.

Boundary conditions setting

Fluid computational domain is shown in Figure 3. Boundary conditions are shown in Table 4. The velocity in the inlet section was set as a fully developed turbulent flow in a pipe, its mean value of 0.13 kg/s; in the outlet section was set at ambient pressure 101325 Pa; on the walls of all the components of the velocity zeroed (condition “sticking”) [6-9].

Additional information:

(a) fixed wall boundary


Adiabatic slip free, fixed temperature wall 293 K, the boundary layer is treated by turbulent wall law.

(b) import and export boundary

Use the parameters in steady flow test, the values shown in Table 4.

Analysis target

The inhomogeneous flow of the front end face of the catalytic converter can produce the phenomenon of vortex flow and air separation, which cause the temperature distribution no uniform, also cause the carrier component damage, and then affect the engine’s



1. Import, 2. oxygen sensor (Pre), 3. Pre-catalytic converter, 4. Main catalytic Converter, 5. oxygen sensor(Main), 6. export

Figure 2: Grid partitioning results.




Figure 3: Fluid computational domain.




Figure 1: 3-D model of the exhaust pipe.

Grid type grid	Grid number
Tetrahedral mesh and prismatic boundary layer grid	692162

Table 1: Shape parameter (mm).

Name	Cell (mil)	Thickness (mm)	Coating (g/ft ²)	Diameter (mm)	Length (mm)
Pre-catalytic converter	600	4	130	101.6	90
Main catalytic converter	400	6	130	101.6	152.4

Table 2: The carrier component parameters.

Name	Data
Pre-catalytic converter inlet pipe diameter	62
Pre-catalytic converter length	90
Main catalytic converter inlet pipe diameter	62
Main catalytic converter length	152.4
Total length	2150

Table 3: Grid partition.

Parameter	Setting
Import	Flow 0.13 kg/s temperature 85°C
Export	Relative pressure 30 KPa
Wall	No slip
Pre-catalytic converter	Porosity 0.81
Main catalytic converter	Porosity 0.75

Table 4: Import and export boundary parameters.

work. Therefore, it is necessary to analyze the flow uniformity index γ , the range is between 0 ~ 1, and the 1 means completely uniform. When γ is more than 0.9, the flow uniformity of the cross section is better.

If the position of the oxygen sensor in the exhaust pipe is not suitable, the oxygen sensor cannot measure the oxygen concentration accurately [10-15]. It will affect the air fuel ratio of the ECU calibration, and directly affect the engine’s power per-formance and emission performance. So it is necessary to use CFD to analyze the flow field around the exhaust pipe.



The CFD analysis process is shown in Figure 4.

Results and Discussion

The computed result of all design variables were analysed and discussed in detail to identify the optimum performance of exhaust pipe. The computed result obtained at different design variables; effects of one design variable on other variables were assessed. Effects of flow rate, pressure, uniformity index were discussed in detail [16].

Flow field analysis

The whole pressure field shows that the fluid pressure decreases along the axis of the tube, and the pressure gradi-ent is obvious in the position of the expanding port and the shrink port. The result is shown as Figure 5.



Pressure field distribution

As shown in Figure 6, near the inlet elbow outside wall, the radial pressure of pre-catalytic converter carrier component is relatively large. Near axis center, the axial pressure of main-catalytic converter carrier component is relatively large [17].

Pressure drop analysis

The main pressure drop detection position of the air flow in the pipe is shown in Figure 7, and the pressure loss value is shown in Table 5.

Velocity field analysis

The Figure 8 shows that when the inlet flow is 0.13 kg/s, the highest flow rate can reach 104.8 m/s, and the velocity mutation mainly occurred in the import (export) conical surface. Fluid through the catalytic converter, Reynolds number $Re < 2000$, is laminar flow state.

As is shown in Figure 9, the maximum speed of the pre-catalytic converter end face is 34.92 m/s, the maximum speed of the main catalytic converter end face is 48.91 m/s, which is less than 100 m/s, that is in accordance with the design requirements.

Oxygen sensor position CFD analysis

The front oxygen sensor is located in the main flow area, which is in accordance with the design requirements; The rear oxygen sensor is located in the main flow area, which is in accordance with the design requirements. The analysis result is shown as Figure 10.

Fluid uniformity analysis

In general, the calculation of the fluid uniformity coefficient γ is only for the end face of catalytic converter. When $\gamma < 0.9$, it is necessary to optimize the import.

After calculation, the fluid uniformity coefficient γ of the main catalytic converter end face is 0.97, and the pre-catalytic converter is 0.696. The results are shown in Figure 11.

Velocity Index is a criterion for judging the radial force of the carrier component, as shown in Figure 12, the calculation method is shown in formula (1~3). Under normal circumstances, when the velocity index $\varepsilon \leq 0.7$, that is in accordance with design requirements, but when the fluid uniformity $\gamma \geq 0.94$, without considering the influence of Velocity Index [18].




Figure 6: Pressure field distribution.




Figure 7: Pressure drop detection position.

Position	Pressure drop data (KPa)
P1	12.57
P2	9.09
P3	21.65

Table 5: Pressure drop.




Figure 8: Velocity field analysis.







Figure 9: Section of velocity distribution.



Parameter	Pre-catalytic converter	Main catalytic converter
Xv, max	408.358	137.256
Xv, mid	392.497	120.36
Yv, max	-109.333	209.776
Yv, mid	-134.719	171.64
L	101.6	101.6
ε	0.589	0.821

Table 6: Velocity index calculation results.

Parameter	Pre-catalytic converter	Main catalytic converter	Total
Pressure drop (KPa)	12.57	9.09	21.65
Fluid uniformity coefficient γ	0.696	0.97	
velocity index ε	0.589	0.821	
The maximum speed	34.92	48.91	

Table 7: Results of comprehensive analysis.

$$\epsilon_x = \frac{2(x_{v,max} - x_{mid})}{L_{major}} \quad (1)$$

$$\epsilon_y = \frac{2(y_{v,max} - y_{mid})}{L_{minor}} \quad (2)$$

$$\epsilon = \sqrt{\epsilon_x^2 + \epsilon_y^2} \quad (3)$$

Velocity Index calculation results are shown in Table 6.

The velocity index ε of the precatalytic converter is 0.589, which is less than 0.7, means that is in accordance with design requirements. Even if the main catalytic converter velocity index ε (0.821) is more than 0.7, but also in accordance with design requirements, because the main catalytic converter fluid uniformity coefficient γ =0.97, is more than 0.94.

The comprehensive analysis of the exhaust pipe is shown in Table 7.

Conclusion

Take integrated analysis of the above test results, and the following conclusions can be drawn:

- (1) The exhaust pipe pressure loss of the catalytic converters is 12.57 kPa, 9.09 kPa, 21.65 kPa, which is in accordance with the design requirements.
- (2) The fluid uniformity coefficient of the inlet end face of the catalytic converter is satisfied.
- (3) The velocity index of the main and the pre catalytic converter meets the design requirements.
- (4) The maximum flow velocity of the pre and main catalytic converter is less than 100 m/s, which meets the design requirements.
- (5) The flow velocity of the oxygen sensor is higher and the oxygen sensor place is more reasonable.

Acknowledgement

The authors thank the Science research project of Hebei Province, Youth Science and Technology Fund of agriculture university of Hebei, and Baoding science and technology research and development plan for support.

References

1. Tao J, Maji L (2012) CFD automatic analysis process of the engine ports. Journal of Wuhan University of Technology 34: 310-312.
2. Zhi W, Ronghua H (2002) Research based on CAD/CAM/ CFD for engine port development. Chinese Internal Combustion Engine Engineering 23: 26-29.
3. Kharkov N, Vatin N, Strelets K (2014) Gas dynamics in a counter-flow cyclone with conical nozzles on the exhaust pipe. Applied Mechanics & Materials: 635-637.
4. Gasser I, Rybicki M (2013) Modelling and simulation of gas dynamics in an exhaust pipe. Applied Mathematical Modelling 37: 2747-2764.
5. Usmanova RR, Zaikov GE, Stoyanov OV, Klodzinska E (2013) Research of the mechanism of shock-interial deposition of dits-persed particles from gas flow. Herald of Kazan Technological University 16: 203-207.
6. Usmanova RR, Zaikov GE (2014) The new equipment for modernization of system of clearing of flue gases Herald of Kazan Technological University 17: 246-251.
7. Usmanova RR, Zaikov GE (2014) Experimental researches and calculation of boundary concentration of an irrigating liquid. Herald of Kazan Technological University 17: 183-187.
8. Usmanova RR, Zaikov GE, Zaikov VG (2008) Calculation of dust separation efficiency of new dising dynamic gas washer. Journal of the Balkan Tribological Association 14: 247-251.
9. Panov AK, Usmanova RR, Zaikov VG, Zaikov GE (2007) Complex aero hydrodynamic research and the effectiveness or arresting dispersed particles for barbotage rotation. Journal of Applied Polymer Science 104: 2088-2091.
10. Vatin NI, Chechevickin VN, Chechevickin AV (2011) About sorp-tion-catalytic air cleaning in premises for people habitation in megapolises. Magazine of Civil Engineering 1: 24-27.
11. Wangwenhai W, Cho HM (2014) A Study on the Fluid Dynamic of Catalytic Converter in Exhaust Pipe", Journal of Energy Engi-neering 23: 114-118.
12. Kumar S, Bergada JM (2013)The effect of piston grooves performance in an axial piston pumps via CFD analysis. International Journal of Mechanical Sciences 66: 168-179.
13. Omidbeygi F, Hashemabadi SH (2013) Exact solution and CFD simulation of magnetorheological fluid purely tangential flow within an eccentric annulus. International Journal of Mechanical Sciences 75: 26-33.
14. Li J, Uttarwar RG, Huang Y (2013) CFD-based modeling and design for energy-efficient VOC emission reduction in surface coat-ing systems. Clean Technologies and Environmental Policy 15: 1023-1032.
15. Chica Arrieta EL, Florez SA, Sierra NI (2013) Application of CFD to the design of the runner of a propeller turbine for small hydroelectric power plants. Rev Fac Ing Univ Antioquia: 181-192.
16. Mitiku Y, Ramayya V, Shunki G (2015) Turbine Driven Pump CFD Modelling and Simulation a Centrifugal Pump Optimization forIrrigation. International Journal of Engineering and Technical Research (IJETR) 3: 154-159.
17. Ramos HM, Simao M, Borga A (2012) CFD and experimental study in the optimization of an enegy converter for low heads. CSCanada. Energy Science and Technology 4: 1029-1035.
18. Nawaz H, Yuan YS (2013) Thermal Comfort Analysis of a Ship Air-Conditioning System Using Solidworks Flow Simulation. Advanced Materials Research 4: 883-888.